

# Generator Drive Applications

Stage V/Final Tier 4 Engines



JOHN DEERE

*Dual frequency engines for worldwide use*





## Confidence is built in

You can count on John Deere PowerTech™ generator drive engines to start in the morning, operate efficiently all day, and work reliably for many years. You also get the confidence of having the John Deere integration and support network at your side every step of the way.

### Prime or standby power

John Deere generator drive engines are ready when and where you need them. They provide fast response for standby situations and exceptional load recovery in a wide variety of applications.

### The power of choice

Why build your gen-set around someone else's engine? With John Deere, you get a wide range of configurations and accessories so you can specify the right generator drive engine that best fits your application. Our preconfigured options can save you hours of engineering time and help you get machines to market faster.

### Integration assistance

You get expert integration assistance provided by John Deere engineers and distributors. OEMs can put our application engineering experience and know-how to work to save development time and money.

### Customer support

With more than 4,000 John Deere service locations worldwide, you never have far to go to find expert assistance and advice.

### Fast parts delivery

Our distributors and dealers stock maintenance parts, as well as many other common replacement parts, to meet your service needs quickly. Our worldwide parts distribution system also provides overnight delivery in most regions.



## Engines for EU Stage V and EPA Final Tier 4 applications

John Deere generator drive engines meet EU Stage V and EPA Final Tier 4 emissions regulations. OEM customers currently using a John Deere Stage IV engine with a DPF won't have to re-engineer the machine design to meet the requirements of Stage V regulations. Both 50 Hz and 60 Hz configurations are EU Stage V and EPA Final Tier 4 certified.

Node	PowerTech name/disp.	Type	Engine model	Power unit model <sup>†</sup>	Speed	Standby ratings			Prime ratings			Generator efficiency	Fan power	Dual freq.	RoHS <sup>†</sup>
					rpm	kWm	kVA	kWe	kWm	kVA	kWe	%	kW		
<b>DOC and DPF aftertreatment</b>															
30	EWX 2.9L	3 cyl.	3029HG530	3029HP530	1500	36	38	31	33	35	28	90	1.8	■	■
					1800	36	38	31	33	35	28	90	1.8	■	■
40	EWX 2.9L	3 cyl.	3029HG530	3029HP530	1500	48	51	41	44	46	37	90	2.4	■	■
					1800	48	51	41	44	46	37	90	2.4	■	■
55	EWX 2.9L	3 cyl.	3029HG530	3029HP530	1500	55	59	47	50	53	43	90	2.8	■	■
					1800	55	59	47	50	53	43	90	2.8	■	■
<b>DOC, DPF, and SCR aftertreatment</b>															
80	EWS 4.5L <sup>**</sup>	4 cyl.	4045HG551	4045HP551	1500	83	91	73	76	82	66	92	4.2	■	■
					1800	86	94	75	78	85	68	92	4.3	■	■
100	EWS 4.5L <sup>**</sup>	4 cyl.	4045HG551	4045HP551	1500	103	113	90	94	102	81	92	5.2	■	■
					1800	106	116	93	96	105	84	92	5.3	■	■
150	PVS 6.8L	6 cyl.	6068HG550	6068HP550	1500	165	182	146	150	165	132	93	8.3	■	■
					1800	180	199	159	164	180	144	93	9.0	■	■
200	PSS 6.8L	6 cyl.	6068CG550	6068CP550	1500	202	223	178	184	202	162	93	10.1	■	■
					1800	216 <sup>**</sup>	239	191	197	216	173	93	10.8	■	■
275	PSS 9.0L	6 cyl.	6090CG550	6090CP550	1500	273	301	241	248	273	218	93	13.7	■	■
					1800	273	301	241	248	273	218	93	13.7	■	■
300	PSS 9.0L	6 cyl.	6090CG550	6090CP550	1500	304	336	269	277	304	243	93	15.2	■	■
					1800	326	360	288	297	326	261	93	16.3	■	■
500	PSS 13.6L	6 cyl.	6136CG550	—	1500	505	557	446	460	505	404	93	25.5	■	■
					1800	505	556	445	460	503	403	93	26.5	■	■

\* Power unit includes factory-mounted cooling package, air filter, and feet.  
 † The majority of John Deere Stage V engines comply with the European Union's Restriction of Hazardous Substances (RoHS) Directive, 2011/65/EU, as amended.  
 \*\* EWS 4.5L is certified to EU Stage V only.  
 †† Rating at 241 kWm is also available.



# The John Deere difference

## Proven performance



### Off-highway experience

John Deere has billions of hours of field experience with off-highway engine technologies.

We use an exhaust system strategy that is designed to be transparent to the operator, without impacting machine performance. Our proven aftertreatment solution has logged more than 1 billion hours of operation on hundreds of internal and external OEM applications.



### Load acceptance

Tailored turbocharging technology provides exceptional load acceptance and block loading capability.

Engines with cooled exhaust gas recirculation (EGR) deliver up to eight times better transient response than non-EGR engines. The potential energy transferred through EGR is immediately available to the turbo to generate boost.

John Deere engines meet ISO 8528-12 Class G3 international standards.

## Reliable uptime



### Day-to-day reliability

John Deere engines feature top-liner cooling, efficient lubrication, and robust cooling systems for reliable operation.



### Long-haul durability

Heavy-duty, oversized components and wet-type cylinder liners provide long engine life.

John Deere engines are designed for rugged applications.



### Extreme conditions

John Deere engines are built to operate in hot and dry, subzero, and humid climates as well as high altitudes. The engine control unit (ECU) monitors and protects engine components in these extreme conditions.

In regions where fuel quality may vary, John Deere protects the engine with two-stage fuel filtration and water detection.

## Efficient operation



### Fuel efficiency

The efficient design of the John Deere combustion chamber with high-ring pistons helps reduce fuel consumption.



### Less DEF

Use of cooled EGR reduces nitrogen oxides (NOx) out of the engine. This enables the use of a smaller selective catalytic reduction (SCR) system and lower diesel exhaust fluid (DEF) consumption. John Deere engines with EGR use 1 to 3 percent less DEF compared to non-EGR engines.



### Low-idle capability

Reduces fluid consumption and decreases wear during transport or startup and shutdown checks.



### Life cycle costs

Reliable operation, low maintenance, long engine life, and exceptional fluid economy lead to low cost of operation with John Deere engines.

## Easy integration



### Preconfigured power units

John Deere engine packages come with mounting pads, cooling package, and air filter for ease of design and installation.



### Dual frequency

Manufacturers that need 50 Hz and 60 Hz power can switch between 1500 and 1800 rpm without reprogramming.

*The majority of John Deere Stage V engines are RoHS compliant for the Restriction of Hazardous Substances in the EU.*





## Integrated Emissions Control system

John Deere has integrated advanced technologies with field-proven solutions to meet each regulatory tier. A single engine control unit (ECU) manages the engine and entire Integrated Emissions Control system.

### Turbocharging

John Deere engines use fixed geometry turbochargers sized for specific power ranges, wastegate turbochargers (WGT) to develop more airflow at lower engine speeds, and variable geometry turbochargers (VGT) to tailor the amount of recirculated exhaust gas that mixes with fresh air. Some models use a fixed turbocharger and VGT in series to deliver higher power density, improved low-speed torque, and excellent high-altitude operation.

### Cooled exhaust gas recirculation (EGR)

Cooled EGR is a proven technology that reduces nitrogen oxides (NOx) by mixing measured amounts of cooled exhaust gas with incoming fresh air to lower the engine's peak combustion temperature.

### Exhaust filters

All engine models that meet Stage V emissions use an exhaust filter with a diesel oxidation catalyst (DOC) and diesel particulate filter (DPF) to provide a reliable solution for reducing particulate matter (PM). This is the accepted technology for reducing PM in nonattainment areas.

### Selective catalytic reduction (SCR)

John Deere Stage V/Final Tier 4 engines feature an SCR system that utilizes a urea-based additive, sometimes referred to as diesel exhaust fluid (DEF). The ammonia in the urea mixes with engine exhaust gases in the SCR catalyst to reduce NOx – converting it to nitrogen and water vapor. This is an accepted technology for reducing NOx in nonattainment areas.

## Always at your side

### Warranty support when you need it

John Deere provides one of the best warranties in the business. Our 2-year/2,000-hour standard warranty applies not only to the new OEM engine but also to John Deere parts and accessories added by a John Deere engine distributor.\*

Register your John Deere OEM engine and enable your John Deere dealer or engine distributor to respond should you need a warrantable repair.† Registering your engine at [JohnDeere.com/OEMWarranty](http://JohnDeere.com/OEMWarranty) gives us the information needed to stock the right service parts, maintenance products, and servicing tools.

\* When sold by John Deere, its authorized dealers and distributors, and delivered to the first retail purchaser.

† See specific OEM product warranty language for applicable terms and conditions. Refer to the John Deere new engine warranty for complete warranty coverage details.

Note: the 2-year/2,000-hour standard warranty and OEM engine registration may not be available in all countries.



### Worldwide locations

#### North America, South America, and Caribbean

John Deere Power Systems  
3801 West Ridgeway Avenue  
P.O. Box 5100  
Waterloo, IA 50704-5100  
Phone: 800-533-6446 (U.S.)  
Phone: 319-292-6060 (Outside the U.S.)  
Fax: 319-292-5075  
Email: [JDPower@JohnDeere.com](mailto:JDPower@JohnDeere.com)

#### Mexico and Central America

Industrias John Deere S.A. de C.V.  
Boulevard Diaz Ordaz No. 500  
Garza Garcia, Nuevo Leon 66210  
Mexico  
Phone: +52-81-8288-1212  
Fax: +52-81-8288-8284  
Email: [MexWeb@JohnDeere.com](mailto:MexWeb@JohnDeere.com)

#### Europe, Africa, Middle East, Australia, and New Zealand

John Deere Power Systems  
Orléans-Saran Unit  
1, rue John Deere – B.P. 11013  
45401 Fleury-les-Aubrais Cedex  
France  
Phone: +33-2-38-82-61-19  
Fax: +33-2-38-84-62-66  
Email: [JDEngine@JohnDeere.com](mailto:JDEngine@JohnDeere.com)

#### Asia

John Deere Asia (Singapore) Pte. Ltd.  
#06-02/03 Alexandra Point  
438 Alexandra Road  
119958 Singapore  
Phone: +65-6879-8800  
Fax: +65-6278-0363  
Email: [JDAsiaEngines@JohnDeere.com](mailto:JDAsiaEngines@JohnDeere.com)







**JOHN DEERE**

*This literature has been compiled for worldwide circulation. While general information, pictures and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL AUTHORIZED JOHN DEERE DEALER OR DISTRIBUTOR FOR DETAILS. John Deere reserves the right to change specification, design and price of the products described in this literature without notice. John Deere's green and yellow color schemes, the leaping deer symbol, and JOHN DEERE are trademarks of Deere & Company.*

