

## Slangdimensioner & vätskevolym Solé & Hyundai-SeasAll

	Bränsle in (mm)	Bränsle ut (mm)	Sjövatten (mm)	Avgas (mm)	Kylsystemrymd (l)	Oljerymd (l)	Hyttvärme in (mm)	Hyttvärme ut (mm)	Sjövatten (L/min,max)
Mini-17	8	5	20	40	3,0	2,9	18	18	29
Mini-29	8	5	20	50	3,0	3,6	18	18	29
Mini-33	8	5	20	50	5,7	4,2	18	18	29
Mini-44	8	5	20	50	8,0	6,0	18	18	29
Mini-55	8	5	26	60	8,0	6,0	18	18	72
SK-60	8	5	32	60	8,5	6,0	18	18	
Mini-62	8	6	32	60	9,5	6,5	18	18	158
Mini-74	8	8	32	75	13,0	9,0	18	18	158
SM-82	8	8	32	75	11,0	10,0	18	18	158
SM-94	8	8	32	75	11,0	10,0	18	18	158
SM-103	8	8	32	75	18,0	11,5	18	18	158
SDZ-165	12	12 *	42	90	17,5	14,0			
SDZ-205	12	12 *	42	125	20,0	21,0			
SDZ-280	12	12 *	42	125	24,0	21,0			

U125	8	8	32	60	5,5	5,7	17,3	17,3	100
D170	8	8	38	90	6,5	6,0	19,3	19,3	147
R200	8	8	38	80	10,5	7,2	19,3	19,3	
S250 & S270	8	8	45	90	13,5	7,7	17,3	17,3	175
H380	10	10	51		43,0	32,0	17,3	17,3	337
L500/600					52,0	42,0			336

\* Om längden på returledningen överstiger 6 m krävs grövre slang (se instruktionsbok)

	Impeller	Water Pump	Flow (L/min)		
			1500 rpm	2500 rpm	3500 rpm
MINI-17	31211008	37611000	18	29	29
MINI-29					
MINI-33					
MINI-44					
MINI-55	35111008	37711000	31	56	72
MINI-62	34711008	36511000	75	122	158
MINI-74					
SM-82-94-103					